

Ink-O-Matic Tester

The Ink-O-Matic Tester is ideal for most retail environments. The Ink-O-Matic Tester tests the circuit and print functions of more than 65 HP, Lexmark and Dell cartridges quickly and easily.



- Tests new and most popular cartridges including HP's 9* series and Lexmark's 3* series.
- Seven Test Stations with room for immediate upgrade when new cartridge models are released.
- Printed test pattern confirms print head function without the need for multiple test printers.
- Testing cartridges is quick and easy – testing can be done without a computer and eliminates the need to change printer preferences each time you test print.
- Minimal Space Required – you'll be able to use your shelves for merchandise instead of test printers!

The Ink-O-Matic Tester circuit and print tests a wide variety of cartridges quickly and easily.

Hewlett Packard

15 (C6615A)	15 (C6615D)	17 (C6625A)	17 (C6625D)
21 (9351A)	22 (9352A)	23 (C1823D)	23 (C1823G)
27 (C8727A)	28 (C8728A)	41 (51641)	40 (51640A)
45 (51645A)	45 (51645G)	56 (C6656A)	57 (C6657A)
78 (C6578A)	78 (C6578D)	92 (9362W)	93 (9361W)
94 (C8765)	95 (C8766)	96 (C8767)	97 (C9363)
130 (C8767)	131 (C8765)	134 (C9363)	135 (C8766)
338 (C8765)	339 (C8767)	343 (C8766)	344 (C9363)
852 (C8765)	853 (C8767)	854 (C9361Z)	855 (C8766)
857 (C9363)	132 (C9362HJ)	136 (C9361HJ)	336 (C9362EE)
342 (C9361EE)			

Lexmark

16 (10N0016)	17 (10N0217)	19 (15M2619)	20 (15M0120)
25 (15M0125)	26 (10N0026)	27 (10N0227)	32 (18C0032)
33 (18C0033)	34 (18C0034)	35 (18C0035)	48 (17G0648)
50 (17G0050)	55 (16G0055)	70 (12A1970)	71 (15M2971)
75 (12A1975)	80 (12A1980)	82 (18L0032)	83 (18L0042)
85 (12A1985)	88 (18L0000)		

Dell

7Y743 (462-0531)	7Y745 (462-0532)	J5566 (310-5372)	J5567 (310-5375)
M4640 (310-5368)	M4646 (310-5371)	T0529 (463-1407)	T0530 (463-1408)

Samsung

Samsung INK M70	Samsung INK C70	Samsung INK M30	Samsung INK C30
Samsung Ink M50	Samsung INK C50	Samsung INK C60	Samsung INK M80
Samsung Ink C80	Samsung INK M90	Samsung INK C90	

Ink-O-Matic Tester Technical Specifications:

Electrical Connection: 110 VAC 50/60 Hz, 1.5 KW

Shipping Weight: 46 lbs / 21 kg

Dimensions (L x W x H): 27" x 15" x 10" / 670 mm x 380 mm x 240 mm

